





Glasswall ICAP Plug-In

Proxy Servers or Application Delivery Controllers are standard elements within the network to separate trust boundaries. Glasswall CDR can be inserted into the transparent SSL inspection of traffic to disarm and rebuild dangerous files.

Key Benefits



Leverage existing Proxy Server to remove threats from files which ingress or egress between trust boundaries without requiring user action or co-operation



Apply CDR policies to web traffic that ensures your business and users are protected, while maintaining business continuity



Industry standard implementation of Internet Content Adaptation Protocol (ICAP) to work with Proxy Servers to yield industrial strength protection for users



Key Features

- CDR protection provided to file transfer with only millisecond latency
- Analysis of files injected from transparent SSL inspection is directed to an open-architecture
- Kubernetes deployment to provide burstable speed and scaling as web and user traffic increases
- Returned files are visually identical to the original file
- Ability to disable HTML links in files to protect users from social engineering attacks that may appear from legitimate file origins
 - Files are rebuilt to a standard format, reducing risk against the most
- sophisticated attacks
- Secures web traffic, without prescribing how a user archives their day-to-day business goals

Use Cases



Cross Domain
Solution where files
are in transit across
trust boundaries



Safety net for users opening files from seemingly trustworthy URLs



Inline security with either a forward or reverse proxy workflow



Where file sandboxes or denotation chambers degrade user experience to become unworkable

How It Works

Network appliances that support the Internet Content Adaptation Protocol (ICAP) provide an industry standard way to support transparent inspection of traffic by Glasswall CDR. Files are processed by Glasswall CDR Platform with millisecond speed and returned free from threats so they can be safely opened and viewed by the user.

